
CONDENSATE DRAIN HEATER ECDH-5


DESCRIPTION

CDH series have been developed to prevent condensate from freezing inside condensate drain ECD housing. It is conducting 5W thermal energy through junction between heater and condensate drain. It can raise the temperature of aluminium housing for up to 15°C, thus allowing the operating temperatures as low as -15°C.



TECHNICAL SPECIFICATION

Voltage	**230 V +/-10%**	
Power	5 VA	
Frequency	50 – 60 Hz	
Power interface	3 x 0,75mm^2	
Protection class	IP67	
Operating temperature	-15 – 45°C	5 – 113 °F
Housing material	Ertalon, epoxy compound	
Heater material	Aluminium	



RESPONSE UNDER LOAD

TEMPERATURE DIFFERENCE

MATERIALS

Housing material	Ertalon, epoxy compound
Heater material	Aluminium
Cable	PVC shell
Screws	Case-hardened, zinc plated, waxed

Omega Air d.o.o. Ljubljana
Cesta Dolomitskega odreda 10
1000 Ljubljana, Slovenia


Tel: +386 (01) 200 68 00
Fax: +386 (01) 200 68 50

e-mail: info@omega-air.si
www.omega-air.si

©Copyright 2010, Omega Air d.o.o.Ljubljana


PARTS LIST

1	Heater housing
2	DIN7500 BN BN3327.1540777 screw



DIMENSIONS

A	70mm
B	65mm
C	19,5mm
D	2m
Volume	0,08l
Mass	180g



MAINTENANCE

Once per year make a visual check of the heater and make sure there is no visual damage.

INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE

BUREAU VERITAS	Our quality management system is certified by BUREAU VERITAS in conformity with ISO 9001:2008 Reg. number: 200285	

Omega Air d.o.o. Ljubljana
Cesta Dolomitskega odreda 10
1000 Ljubljana, Slovenia

Tel: +386 (01) 200 68 00
Fax: +386 (01) 200 68 50

e-mail: info@omega-air.si
www.omega-air.si

©Copyright 2010, Omega Air d.o.o.Ljubljana