

Claw Couplings

Left-Closing and Coloured



- Robust couplings of malleable iron or steel zinc-plated and yellow passivated (free of chrome VI) with safety notches and locking nut on female claw couplings left closing
- 100 % couple-test and sight control
- With oil-resistant rubber ring SGOR-N, on request with steam-resistant rubber ring SDOR-N (up to 200°C) or with brass seal and standard seal
- Through left-closing mechanism the couplings can't be connected with standard claw couplings (right-closing), additional warning through ears at the claws or colour
- **Mainly used in chemical and petrochemical plants to avoid connection of different fluids, f.e compressed air, steam, gas media, nitrogen**

Materials

- Claw: Malleable iron zinc-plated and yellow passivated (free of chrome VI)
- Connector: Steel zinc-plated and yellow passivated (free of chrome VI)
- Locking nut: Brass MS 58 plain
- O-rings: Buna N/ Brass

Max. Working Pressure	Temperature	Thread	Claw Distance	Media	
PN 16 bar	-40°C – +95°C	ISO 228	42 mm	various	1

Hose Claw Couplings left-closing

Hose connection	L	B	L1	Passage	Typ	Version	Seal	Weight	Type No.
Hose i.D. 19	100	85	41	16	MODY	w safety collar	Buna N	340	SSGL 19
Hose i.D. 19	112	85	40.5	16	MODY	w safety collar	Buna N	367	SSGL 19 S
Hose i.D. 19	84	85	49	16	MS-seal	w/o safety collar	Brass	240	SKML 19

Other sizes on request.

For hose clamps DIN 20039 A or B (☺ page 413)

Female Claw Couplings left-closing

Thread connection	L	SW	B	L1	Passage	Typ	Seal	Weight	Type No.
G 3/4 f	38	40	85	16	20	Standard	Buna N	210	KIGL 34
G 3/4 f	93	32	85	20	19	MODY	Buna N	434	SSGL 34
G 1 f	39	40	85	18	20	Standard	Buna N	180	KIGL 10

Other sizes on request.

Male Claw Couplings left-closing

Thread connection	L	SW	B	L1	Passage	Typ	Seal	Weight	Type No.
G 3/4 m	73	24	85	15	19	MODY	Buna N	339	SSGAL 34

Other sizes on request.

Original Standard-Rubber Rings

(☺ page 239)

Original MODY-Rubber Rings - Standard Version





(☺ page 233)

Original MODY-Rubber Rings - Old Version

(☺ page 233)

Original Spare Parts for Claw Couplings with Brass Seal

Type	L	D	D1	Material		Weight	Type No.
Brass sleeve	21	32	17	Brass	10	12.5	MOOH
Hose ring	12	28	23	Buna N	100	3.2	SOOR
Steel screw M5	14	7	-	Steel zinc-pl. + yellow pass.	100	2	HOOS



All types also available coloured (powder-coated) against surcharge!

RAL 5010
 RAL 6029
 RAL 1004
 RAL 2002
 ...others on request.

® At least 100 pc/type necessary!

C L A W C O U P L I N G S