


Connecting Nipples

- Nipples of steel or malleable iron, zinc-plated and yellow passivated (free of chrome VI)
- Suitable for screwings (☉ page 246 - 248) DIN 8537/20033
- **Worldwide used system for compressed air, water etc. in construction, mining and tunneling**

Materials:

- Connecting nipples: Steel or malleable iron zinc-plated and yellow passivated (free of chrome VI)




Max. Working Pressure	Thread	Media
PN 25 bar	ISO 228 / DIN 405	Compressed air / water

Double Nipples DIN 8537/20036

Thread connection	L	SW	L1	Cone		Weight	Type No.
2 x G 3/4 m	47	27	19	2 x 1:4	10	107	V 34 N
2 x G 3/4 m	47	32	19	2 x 1:4	10	125	V 34-32 N
2 x G 1 m	55	36	23	2 x 1:3	10	197	V 10 N
2 x Rd 32x1/8 m	55	32	23	2 x 1:3	10	163	V 32 N
2 x Rd 38x1/8 m	62	41	26	2 x 1:3	10	283	V 38 N
2 x Rd 46x1/6 m	70	46	30	2 x 1:3	1	410	V 46 N
2 x Rd 55x1/6 m	78	55	32	2 x 1:3	1	648	V 55 N
2 x Rd 62x1/6 m	88	65	36	2 x 1:3	1	869	V 62 N
2 x Rd 75x1/6 m	100	75	41	2 x 1:3	1	1490	V 75 N
2 x Rd 105x1/6 m	122	105	51	2 x 1:3	1	2990	V 105 N

Sieve Nipples DIN 20037

Thread connection	L	SW	L1	L2	Cone	Sieve		Weight	Type No.
G 3/8 m - G 3/4 m	38	27	10	19	1:4	inner	10	84	N 38 IS
G 1/2 m - G 3/4 m	40	27	12.5	19	1:4	inner	10	85	N 23 IS
G 1/2 m - Rd 32x1/8 m	44	32	12.5	23	1:3	inner	10	126	N 82 IS
G 3/4 m - G 3/4 m	44	27	16	19	1:4	inner	10	104	N 34 IS
G 3/4 m - G 3/4 m	44	32	16	19	1:4	inner	10	120	N 34-32 IS
G 3/4 m - Rd 32x1/8 m	48	32	16	23	1:3	inner	10	135	N 32 IS
G 3/4 m - G 1 m	48	36	16	22	1:3	inner	10	173	N 341 IS
G 3/4 m - G 3/4 m	44	27	16	23	1:4	outer	10	100	N 34 AS
G 3/4 m - G 3/4 m	44	32	16.5	19	1:4	outer	10	120	N 34-32 AS
G 3/4 m - Rd 32x1/8 m	48	32	16.5	19	1:3	outer	10	130	N 32 AS
G 3/4 m - Rd 32x1/8 m	48	32	16.5	23	1:3	without	10	142	N 32 OS
G 1 m - Rd 32x1/8 m	49	36	16	22	1:3	inner	10	193	N 132 IS
G 1 m - Rd 34x1/8 m	54	41	18	26	1:3	without	10	252	N 18 OS
G 1 m - Rd 46x1/6 m	58	46	18	30	1:3	without	1	345	N 46-10 OS
G 1 1/4 m - Rd 46x1/6 m	58	46	18	30	1:3	without	1	331	N 46-54 OS
G 1 1/2 m - Rd 46x1/6 m	63	50	23	30	1:3	without	1	445	N 46 OS
G 1 1/4 m - Rd 55x1/6 m	63	55	18	32	1:3	without	1	536	N 55-54 OS
G 1 1/2 m - Rd 55x1/6 m	68	55	23	32	1:3	without	1	529	N 55 OS
G 2 m - Rd 55x1/6 m	70	65	25	32	1:3	without	1	860	N 55-20 OS
G 1 1/2 m - Rd 62x1/6 m	75	65	23	36	1:3	without	1	764	N 62 OS
G 2 m - Rd 62x1/6 m	75	65	25	36	1:3	without	1	820	N 62-20 OS
G 1 1/2 m - Rd 75x1/6 m	80	75	23	41	1:3	without	1	1220	N 75-15 OS
G 2 m - Rd 75x1/6 m	85	75	28	41	1:3	without	1	1196	N 75 OS
G 2 1/2 m - Rd 75x1/6 m	85	75	28	41	1:3	without	1	1387	N 75-25 OS
G 3 m - Rd 105x1/4 m	100	105	29	51	1:3	without	1	2290	N 105 OS



Connecting Nipples

Thread connection	L	SW	L1	L2	Cone		Weight	Type No.
G 3/4 f - G 3/4 m	44	32	19	19	1:4	10	126	A 34 N
G 3/4 f - G 1 m	48	36	23	19	1:3	10	200	A 3410 N
G 3/4 f - Rd 32x1/8 m	47	32	21.5	19	1:3	10	136	A 32 N
G 3/4 f - Rd 38x1/8 m	48	41	25	19	1:3	10	270	A 38 N
G 1 f - Rd 32x1/8 m	50	41	23	22	1:3	10	206	A 1032 N
G 1 f - Rd 38x1/8 m	52	41	25	22	1:3	10	239	A 10 N

