



Connecting Nipples

Self-locking Nipple with brass valve

Thread connection	L	SW	Cone		Weight	Type No.
G 3/4 m - Rd 32x1/8 m	49	32	1:3	10	153	SN 32 ST

Combination Nipple

Thread connection	L	SW	L1	L2	Cone		Weight	Type No.
G 1 m - G 3/4 m	51	36	23	19	1:4	10	179	V 1034 N



Hot Tar Screwing

- Hot tar screwing of steel/malleable iron, zinc-plated and yellow passivated (free of chrome VI)
- Easy to screw through wing nut; tapered Stem with safety collar
- [For hose connection on hot tar spraying devices, hot tar lances a.o.](#)

Materials:

- Tapered stem: Steel zinc-plated and yellow passivated (free of chrome VI)
- Wing nut: malleable iron zinc-plated and yellow passivated (free of chrome VI)
- Nipple: Steel zinc-plated and yellow passivated (free of chrome VI)

Max. Working Pressure	Thread	Media	
PN 25 bar	ISO 228	hot tar	1

Hot Tar Screwing

Type	Connection	L	B	SW	L1	Passage	Weight	Type No.
Hot tar screwing complete	Hose i.D. 3/4 x G 3/4 f	112	165	32	60	15	506	HTV-SB*
Tapered stem	Hose i.D. 3/4, Cone 1:3					15	200	HTVT-SB*
Wing nut	G 1 1/4 f					-	207	HTVM
Nipple	G 3/4 f x G 1 1/4 m, Cone 1:3					-	99	HTVET

For hose clamps DIN 20039 B, type SK 34 (© page 413)

Other sizes on request.

*with safety collar

