

Materials

- Connecting nut: Malleable iron zinc-plated and yellow passivated (free of chrome VI)
- Tapered stem: Steel zinc-plated and yellow passivated (free of chrome VI)
- O-ring: Buna N

Tapered stems of steel

Hose connection	L	B	Cone		Weight	Type No.
Hose i.D. 13	79	24	1:4	10	74	T 13 B
Hose i.D. 15	79	24	1:4	10	72	T 15 B
Hose i.D. 19	80	24	1:4	10	94	T 19 B

Hose i.D. 13	80	28	1:3	10	104	ST 13 B
Hose i.D. 15	80	28	1:3	10	83	ST 15 B
Hose i.D. 19	80	28	1:3	10	100	ST 19 B
Hose i.D. 19	80	28	1:3	10	105	ST 19 B-PH*

Hose i.D. 13	80	28	1:3	10	104	ST 13 B
Hose i.D. 15	80	28	1:3	10	83	ST 15 B
Hose i.D. 19	80	28	1:3	10	100	ST 19 B
Hose i.D. 19	80	28	1:3	10	109	ST 19 B-PH*

Hose i.D. 25	85	29	1:3	10	163	ST 25 B/3
--------------	----	----	-----	----	-----	-----------

Hose i.D. 25	85	30	1:3	10	148	ST 25 B/2
--------------	----	----	-----	----	-----	-----------

Hose i.D. 25	90	33	1:3	10	164	ST 25 B
Hose i.D. 25	88.5	33	1:3	10	200	ST 25 B-PH*

Hose i.D. 32	120	40	1:3	1	355	ST 32 B
--------------	-----	----	-----	---	-----	---------

Hose i.D. 38	125	48	1:3	1	465	ST 38 B
Hose i.D. 38	110	48	1:3	1	420	ST 38 B-PH*

Hose i.D. 42	130	57	1:3	1	558	ST 42 B
--------------	-----	----	-----	---	-----	---------

Hose i.D. 50	140	68	1:3	1	896	ST 50 B
Hose i.D. 53	140	68	1:3	1	947	ST 53 B

Hose i.D. 75	189	98	1:3	1	1990	ST 75 B
--------------	-----	----	-----	---	------	---------

For hose clamps DIN 20039 A, type SL (☺ page 413)

*for hydraulic crimping with socket (☺ page 261)

other types also available on request!

