Hose Clamps
Standard Version

- Robust clamps made of malleable iron, zinc plated and yellow passivated (free of chrome VI) or stainless steel 1.4401
- Robust, easy and secure, for various fittings and applications


Materials
- Clamps, Spacers: Malleable iron zinc-plated and yellow passivated (free of chrome VI)/ Stainless steel 1.4401
- Screws: Galvanized steel/ Stainless steel A4-70

Max. Working Pressure	Norm
PN 16 / 25 bar	DIN 20039 A/B



Hose Clamps, made of malleable iron, two parts with overlapping cast-on-spacers

Version	Hose-o.D./ Range	L	B	Screw size		Weight	Type No.
Hose i.D. 13	22-29	60	17	M 8x30	10	95	S 22
Hose i.D. 19	27-32	70.5	17	M 8x30	10	105	S 34



Hose Clamps DIN 20039 A, made of stainess steel 1.4401, two parts with loose spacers

Version	Hose-o.D./ Range	L	B	Screw size		Weight	Type No.
Hose i.D. 13	18-26	63	18	M 8x30	5	140	SLE 13
Hose i.D. 19	26-33	71	18	M 8x30	5	160	SLE 19
Hose i.D. 25	32-40	81	18	M 10x35	5	210	SLE 25




Hose Clamps DIN 20039 A, made of malleable iron, two parts with loose spacers

Version	Hose-o.D./ Range	L	B	Screw size		Weight	Type No.
Hose i.D. 13	22-29	63	18	M 8x30	10	128	SL 29*
Hose i.D. 19	28-34	71	18	M 8x30	10	134	SL 34*
Hose i.D. 25	32-40	81	18	M 10x35	10	188	SL 40*
Hose i.D. 32	39-49	91	20	M 10x35	10	244	SL 49*
Hose i.D. 38	48-60	108	24	M 10x45	5	297	SL 60*
Hose i.D. 50	56-72	116	25	M 10x50	5	340	SL 72
Hose i.D. 50	60-76	127	25	M 10x50	5	405	SL 76*
Hose i.D. 63	77-94	146	30	M 12x55	5	556	SL 94*
Hose i.D. 75	73-94	139	25	M 12x110	1	665	SL 400
Hose i.D. 75	94-115	176	35	M 12x65	1	739	SL 115
Hose i.D. 89	113-127	170	27	M 12x110	1	890	SL 525
Hose i.D. 89	115-145	198	38	M 12x80	1	1046	SL 145
Hose i.D. 100	127-140	178	28	M 12x110	1	972	SL 550
Hose i.D. 100	135-155	194	27	M 12x110	1	984	SL 600
Hose i.D. 125	155-175	217	30	M 12x125	1	1130	SL 675
Hose i.D. 150	175-195	244	30	M 12x125	1	1445	SL 769
Hose i.D. 175	210-225	280	35	M 16x150	1	2163	SL 875
Hose i.D. 200	227-250	312	35	M 16x150	1	2610	SL 988

*according to DIN 20039 A





Hose Clamps DIN 20039 B, made of malleable iron, two parts with loose spacers and safety claws***

Version	Hose-o.D./ Range	L	B	Screw size		Weight	Type No.
Hose i.D. 13	22-29	63	18	M 8x30	10	142	SK 29
Hose 19x2		63	18	M 8x30	10	140	SK 29 FL**
Hose i.D. 19	28-32	77	21	M 10x35	10	220	SK 34
Hose 25x2		77	21	M 10x35	10	220	SK 34 FL**
Hose i.D. 25	35-42	90	22	M 10x35	10	272	SK 39
Hose i.D. 28	42-45	98	24	M 10x35	5	340	SK 44
Hose i.D. 35	45-53	108	25	M 10x45	5	380	SK 51
Hose i.D. 42	55-60	119	26	M 10x45	1	416	SK 60
Hose i.D. 50	60-73	132	30	M 12x55	1	637	SK 73
Hose i.D. 75	86-102	160	28	M 12x55	1	860	SK 75

**for flat hose

***PN 25 bar



