

WaterProfi Claw Couplings and Spray Nozzle

made of Brass for Water Applications



WaterProfi by LUDECKE

WaterProfi MODY-Safety-Screwing-Claw Couplings with hose barb

Hose connection	L	B	L1	Passage	Weight	Type No.
Hose i.D. 13	77	53.5	42	10	190	GSSG 13
Hose i.D. 19	82	53.5	42	16.5	215	GSSG 19
Hose i.D. 25	86	53.5	42	20	270	GSSG 25

For hose clips type HS (☹ page 415), type ZOS (☹ page 414) or crimping ferrules type LPH (☹ page 418)

Thread types on request (GSSGA 34 available from stock)



Original Rubber Ring with support ring of brass for MODY-Safety-Screwing- Claw Couplings of brass

Resistance	L	D	D1	Material	Temp.°C	Media	Colour	Shore A		Weight	Type No.
Water	7	33.5	21.5	NBR/MS	+95	Water	black	65°	10	6	GSGOR-Set



Classic WaterProfi Spray Nozzles of brass – conical sealing brass to brass (PN 10 bar)

Hose connection	L	Ø Nozzle bore	Weight	Type No.
Hose i.D. 13	100	5	115	SDT 13
Hose i.D. 19	112	6.5	245	SDT 19
Hose i.D. 25	125	7	370	SDT 25



Connection	L	Ø Nozzle bore	Weight	Type No.
WaterProfi Coupling	98	5	220	SDK 12
WaterProfi Coupling	113	6.5	310	SDK 34
WaterProfi Coupling	121	7	410	SDK 10



System-Adapter WaterProfi Claw Coupling - Quick Connect Coupling DN 9

Connection	L	B	Weight	Type No.
WaterProfi Claw Coupling - Coupling WS DN 9	76.5	54.2	254	WSK-WPA
WaterProfi Claw Coupling - Plug WS DN 9	59.5	54.2	160	WSS-WPA