


OXYGEN VERTICAL AIR VESSELS





DIRECTIVE	2014/68/UE (PED)	2014/68/UE (PED)
OPERATING PRESSURE	11 BAR	12 BAR
OPERATING TEMPERATURE	-20 +50°C	-20 +80°C



- MATERIAL: CARBON STEEL
- FLUID CONTENT: OXYGEN (GROUP 1 - HYDROGEN AND WATER EXCLUDED)
- FINISHING: EXTERNAL RAL 9010 WHITE PAINT AND INTERNAL RAL 5005 CORROSION-RESISTANT ALM PAINT
- UPON REQUEST: INSPECTION PORTS - 100X150 MM HANDHOLE - 300X400 MM MANHOLE

CODE	Directive	Capacity	Operating pressure	De	A	B	C	L	1	2	3	4	5	6	7	Weight
RAL 9010/RAL 5005		Lt	Bar	mm	mm	mm	mm	mm	inch	inch	inch	inch	inch	inch	inch	Kg
VEC02176	**2014/68/UE (PED)**	**500**	11	600	155	785	1665	2050	2"	2"	2"	-	3/8"	2"	2"	**116**
VEC01719	**2014/68/UE (PED)**	**1000**	12	800	145	770	1720	2350	2"	2"	2"	3/8"	3/8"	2"	2"	**210**
VEC01720	**2014/68/UE (PED)**	**1500**	12	1000	170	680	1780	2305	2"	2"	2"	1/2"	1/2"	2"	2"	**320**
VEC01721	**2014/68/UE (PED)**	**2000**	12	1100	200	770	1970	2490	2"	2"	2"	1/2"	1/2"	2"	2"	**388**
VEC01722	**2014/68/UE (PED)**	**3000**	12	1200	140	830	2250	2990	2"	2"	2"	1/2"	1/2"	2"	2"	**594**
VEC01723	**2014/68/UE (PED)**	**4000**	12	1450	225	800	2145	2790	2"	3"	3"	3/4"	3/8"	3"	3"	**835**
VEC01724	**2014/68/UE (PED)**	**5000**	12	1450	225	800	2745	3390	2"	3"	3"	3/4"	3/8"	3"	3"	**962**