


OMEGA
AIR

ALTERNATIVE FILTER ELEMENTS

ATLAS COPCO NAUTILUS

ATLAS COPCO NAUTILUS Plastic end caps	DD	PD	QD
			
Particle retention	0,1 µm	0,01 µm	activated carbon
Solids - q. class (ISO 8573-1)	2	1	1*
Oils -q. class (ISO 8573-1)	2	1	1
Filter media	borosilicate micro fibres		activated carbon
Operating temp. range [°C]	1,5 to 65	1,5 to 65	1,5 to 45
Diff. pressure (new) [mbar]	50	80	60

	DD		PD		QD	
	ATLAS COPCO	OMEGA AIR	ATLAS COPCO	OMEGA AIR	ATLAS COPCO	OMEGA AIR
	9+ DD	OAC +9 DD/M	9+ PD	OAC +9 PD/S	9+ QD	OAC +9 QD/A
	15+ DD	OAC +15 DD/M	15+ PD	OAC +15 PD/S	15+ QD	OAC +15 QD/A
	25+ DD	OAC +25 DD/M	25+ PD	OAC +25 PD/S	25+ QD	OAC +25 QD/A
	45+ DD	OAC +45 DD/M	45+ PD	OAC +45 PD/S	45+ QD	OAC +45 QD/A
	60+ DD	OAC +60 DD/M	60+ PD	OAC +60 PD/S	60+ QD	OAC +60 QD/A
	100+ DD	OAC +100 DD/M	100+ PD	OAC +100 PD/S	100+ QD	OAC +100 QD/A
	140+ DD	OAC +140 DD/M	140+ PD	OAC +140 PD/S	140+ QD	OAC +140 QD/A
	180+ DD	OAC +180 DD/M	180+ PD	OAC +180 PD/S	180+ QD	OAC +180 QD/A
	220+ DD	OAC +220 DD/M	220+ PD	OAC +220 PD/S	220+ QD	OAC +220 QD/A
	310+ DD	OAC +310 DD/M	310+ PD	OAC +310 PD/S	310+ QD	OAC +310 QD/A
	425+ DD	OAC +425 DD/M	425+ PD	OAC +425 PD/S	425+ QD	OAC +425 QD/A
	550+ DD	OAC +550 DD/M	550+ PD	OAC +550 PD/S	550+ QD	OAC +550 QD/A

* Valid if "S" filter cartridge is installed upstream.



ALTERNATIVE FILTER ELEMENTS

ATLAS COPCO

	DD	PD	QD
ATLAS COPCO Plastic end caps			
Particle retention	0,1 µm	0,01 µm	activated carbon
Solids - q. class (ISO 8573-1)	2	1	1**
Oils -q. class (ISO 8573-1)	2	1	1
Filter media	borosilicate micro fibres		activated carbon
Operating temp. range [°C]	1,5 to 65	1,5 to 65	1,5 to 45
Diff. pressure (new) [mbar]	50	80	60

	DD		PD		QD	
	ATLAS COPCO	OMEGA AIR	ATLAS COPCO	OMEGA AIR	ATLAS COPCO	OMEGA AIR
DD 9		OAC 9 DD/M	PD 9	OAC 9 PD/S	QD 9	OAC 9 QD/A
DD 17		OAC 17 DD/M	PD 17	OAC 17 PD/S	QD 17	OAC 17 QD/A
DD 32		OAC 32 DD/M	PD 32	OAC 32 PD/S	QD 32	OAC 32 QD/A
DD 44		OAC 44 DD/M	PD 44	OAC 44 PD/S	QD 44	OAC 44 QD/A
DD 60		OAC 60 DD/M	PD 60	OAC 60 PD/S	QD 60	OAC 60 QD/A
DD 120		OAC 120 DD/M	PD 120	OAC 120 PD/S	QD 120	OAC 120 QD/A
DD 150		OAC 150 DD/M	PD 150	OAC 150 PD/S	QD 150	OAC 150 QD/A
DD 175		OAC 175 DD/M	PD 175	OAC 175 PD/S	QD 175	OAC 175 QD/A
DD 260/DD 280		OAC 260 DD/M*	PD 260/PD 280	OAC 260 PD/S*	QD 260/QD 280	OAC 260 QD/A*
DD 390		OAC 390 DD/M	PD 390	OAC 390 PD/S	QD 390	OAC 390 QD/A
DD 520		OAC 520 DD/M	PD 520	OAC 520 PD/S	QD 520	OAC 520 QD/A

* Aluminium end caps

** Valid if "S" filter cartridge is installed upstream.