


Industrial Quick Connect Couplings

Series ESAI single shut-off

DN5.5



Plug Profile (original size)

- According to ISO 6150 B resp. US Mil. Spec. 4109
- High-quality, extreme robust quick connect couplings with superior seal characteristic
- High flow rate at a low pressure drop due to streamlined valve
- Special versions on request i.e. couplings with squeeze nut
- **For the supply of compressed as well as air other fluid or gaseous media in industry and craftsmanship**

Materials

- Body, valve body, valve: Brass MS 58 nickel-plated
- Sleeve, plug: Steel hardened and nickel-plated
- O-rings: Buna N (other materials on request)
- Springs: Stainless steel 1.4310
- Balls: Stainless steel 1.4034

Max. Work. Pressure	Temperature	DN	Thread	Flow Capacity	Operation	Type of valve	Media	Area	
PN 35 bar	-20°C – +100°C	5.5	ISO 228 / DIN 2999	1100 l/min	One-Hand	Single Shut-Off	Compr. Air	USA, F, SP	Coupl. 5 / Plug 10

Couplings with tapered male thread (thread coated)

Thread connection	L	SW	D	L1	Weight	Type No.
R 1/4 m	60	19	23	11	95	ESAI 14 A
R 3/8 m	60	19	23	12	98	ESAI 38 A
R 1/2 m	63	22	23	17	120	ESAI 12 A

Couplings with parallel female thread

Thread connection	L	SW	D	L1	Weight	Type No.
G 1/4 f	57	19	23	10	110	ESAI 14 I
G 3/8 f	57	19	23	10	105	ESAI 38 I
G 1/2 f	59	24	23	12	120	ESAI 12 I

Couplings with hose barb

Hose connection	L	SW	D	L1	Weight	Type No.
SLW 6	73	19	23	25	92	ESAI 6 T
SLW 8	73	19	23	25	95	ESAI 8 T
SLW 9	73	19	23	25	96	ESAI 9 T
SLW 10	73	19	23	25	99	ESAI 10 T
SLW 13	73	19	23	25	105	ESAI 13 T

For hose clips type ZOS (© page 414), type HS (© page 415) or crimping ferrules type LPH (© page 418)

Plugs with tapered male thread (thread coated)

Thread connection	L	SW	L1	L2	Weight	Type No.
R 1/8 m	38	13	9	24	19	ESAI 18 NAS
R 1/4 m	41	14	12	24	25	ESAI 14 NAS
R 3/8 m	42	17	13	24	35	ESAI 38 NAS
R 1/2 m	48	22	17	24	55	ESAI 12 NAS

Plugs with parallel female thread

Thread connection	L	SW	L1	L2	Weight	Type No.
G 1/8 f	36	14	9	24	22	ESAI 18 NIS
G 1/4 f	36	17	9	24	25	ESAI 14 NIS
G 3/8 f	36	19	9	24	25	ESAI 38 NIS
G 1/2 f	39	24	12	24	40	ESAI 12 NIS

Plugs with hose barb

Hose connection	L	D	L1	L2	Weight	Type No.
Hose i.D. 6	48	14	23	24	15	ESAI 6 SS
Hose i.D. 8	48	14	23	24	17	ESAI 8 SS
Hose i.D. 9	48	14	23	24	18	ESAI 9 SS
Hose i.D. 10	48	14	23	24	20	ESAI 10 SS
Hose i.D. 13	48	14	23	24	25	ESAI 13 SS

For hose clips type ZOS (© page 414), type HS (© page 415) or crimping ferrules type LPH (© page 418)

