

Quick Connect Couplings


single shut-off Series ESO

- Closed sleeve protects the couplings from dirt, new sleeve profile
- Stem profile for safe fit of the hose and easy assembly
- For compressed air lines in industry, craftsmanship, hobbies, etc.
- Interchangeable to ARO 210, ORION 44510

Materials

- Body, sleeve, valve body, valve, plug: Brass MS 58 plain
- Springs, retaining ring: Stainless steel 1.4310
- Pins: Stainless steel 1.4305
- O-rings: Buna N

DN5.5




Plug Profile (original size)

Max. Work. Pressure	Temperature	DN	Thread	Flow Capacity	Operation	Type of valve	Media	Area	
PN 35 bar	-20°C – +100°C	5.5	ISO 228	775 l/min	One-Hand	Single Shut-Off	Compr. Air	BeNeLux, CH	10

Couplings with male thread


Thread connection	L	SW	D	L1	Weight	Type No.
G 1/4 m	42	22	27	9	85	ESO 14 A
G 3/8 m	43	22	27	10	90	ESO 38 A
G 1/2 m	43	24	27	10	105	ESO 12 A

Male thread sealing with PVC-packing rings type HPD (☺ page 231)



Couplings with female thread


Thread connection	L	SW	D	L1	Weight	Type No.
G 1/4 f	43	22	27	10.5	104	ESO 14 I
G 3/8 f	43	22	27	10.5	108	ESO 38 I
G 1/2 f	44.5	24	27	12	120	ESO 12 I



Couplings with hose barb

Hose connection	L	D	L1	Weight	Type No.
Hose i.D. 6	57	27	25	77	ESO 6 T
Hose i.D. 8	57	27	25	80	ESO 8 T
Hose i.D. 9	57	27	25	82	ESO 9 T
Hose i.D. 10	57	27	25	85	ESO 10 T


For hose clips type ZOS (☺ page 414), type HS (☺ page 415) or crimping ferrules type LPH (☺ page 418)



Plugs with male thread


Thread connection	L	SW	L1	L2	Weight	Type No.
G 1/8 m	33	13	6	22	16	ESO 18 NA
G 1/4 m	35	17	8	22	21	ESO 14 NA
G 3/8 m	35	19	8	22	26	ESO 38 NA

Male thread sealing with PVC-packing rings type HPD (☺ page 231)



Plugs with female thread


Thread connection	L	SW	L1	L2	Weight	Type No.
G 1/4 f	34	17	9	22	23	ESO 14 NI
G 3/8 f	34	19	9	22	23	ESO 38 NI



Plugs with hose barb

Hose connection	L	D	L1	L2	Weight	Type No.
Hose i.D. 6	47	11	22	22	14	ESO 6 S
Hose i.D. 8	47	11	22	22	15	ESO 8 S
Hose i.D. 9	47	11	22	22	16	ESO 9 S
Hose i.D. 10	47	11	22	22	18	ESO 10 S

For hose clips type ZOS (☺ page 414), type HS (☺ page 415) or crimping ferrules type LPH (☺ page 418)



Special versions on request.