


# Temperature Regulation Quick Connect Couplings

## Series ESHMTE plug size 9 mm – Stainless Steel with Automatic Locking Mechanism

**DN6**


Plug Profile (original size)

**Temp  
Secure**  
by LUDECKE

 European  
Plug Profile


- Forced guidance design with visual colour coding at the locking sleeve
- Combined pressure-torsion spring and very robust locking sleeve made of stainless steel
- For temperature regulation applications with hot or cold water as well as tempered oil i.e. in clean-room production
- Optional with straight-through, single or double shut-off
- Versions with additional O-ring sealing at connection port to prevent leakage in high temperature applications

### Materials

- Body, sleeve, valve body, valve, plug: stainless steel 1.4305
- Springs, retaining ring: Stainless steel 1.4310
- Balls: Stainless steel 1.4034
- O-rings: Special-Hitec-FKM-O-ring

Max. Working Pressure	Temperature	DN	Thread	Operation	Type of valve	Media	
PN 15 bar	-20°C – +200°C	6	ISO 228/ DIN 13	One-hand	single/double/straight-thr.	Tempered media	5

### Couplings with hose connection

#### Couplings with straight standard hose stem without/with valve

Hose connection	L	D	L1	DS	Passage	Weight	Type No. w/o valve	Type No. w valve
Hose i.D. 9	61	18	22.5	9	6	54	ESHMTE 9 TL	ESHMTE 9 TLAB

#### Couplings with 45° standard hose stem without/with valve

Hose connection	L	D	L1	DS	Passage	Weight	Type No. w/o valve	Type No. w valve
Hose i.D. 9	54	18	22.5	9	6	79	ESHMTE 9 TL45	ESHMTE 9 TL45AB

#### Couplings with 90° standard hose stem without/with valve

Hose connection	L	D	L1	DS	Passage	Weight	Type No. w/o valve	Type No. w valve
Hose i.D. 9	56	18	22.5	9	6	88	ESHMTE 9 TL90	ESHMTE 9 TL90AB

### Couplings with male threads

#### Couplings with straight male thread without/with valve (inner cone DIN 3863)

Thread connection	L	SW	D	L1	DS	Passage	Weight	Type No. w/o valve	Type No. w valve
G 1/4 m	56.5	17	18	11	9	6	67	ESHMTE14AL	ESHMTE14ALAB
M 14x1.5 m	56.5	17	18	11	9	6	68	ESHMTE1415AL	ESHMTE1415ALAB

#### Couplings with 45° male thread without/with valve (inner cone DIN 3863)

Thread connection	L	SW	D	L1	DS	Passage	Weight	Type No. w/o valve	Type No. w valve
G 1/4 m	52	17	18	11	9	6	83	ESHMTE14AL45	ESHMTE14AL45AB
M 14x1.5 m	52	17	18	11	9	6	84	ESHMTE1415AL45	ESHMTE1415AL45AB

#### Couplings with 90° male thread without/with valve (inner cone DIN 3863)

Thread connection	L	SW	D	L1	DS	Passage	Weight	Type No. w/o valve	Type No. w valve
G 1/4 m	56	17	18	11	9	6	92	ESHMTE14AL90	ESHMTE14AL90AB
M 14x1.5 m	56	17	18	11	9	6	93	ESHMTE1415AL90	ESHMTE1415AL90AB

other types / sizes on request!