
Drain Adaptor

with 3 Automatic-Run-Out-Valves 3/4“ and 2 fixing spears



- High-quality drain adaptor made of stainless steel 1.4401
- Drains the lines automatically when installation is switched off and pressure drops to avoid frost damages on plant and hose lines
- Simply assemble the adaptor at the lowest point between snow pump and hydrant and fix it with two spears (60 cm long) in suitable position

Materials:

- Body: Stainless Steel 1.4401
- Valve: Brass MS 58 nickel-plated
- Seals: Buna N

Snow Master by LÜDECKE

Max. Working Pressure	Temperature	Media	
PN 60 bar	-40°C – +95°C	liquid media	1



Drain-Adaptor with 3 Automatic-Run-Out-Valves 3/4“ and 2 fixing spears

Connection	Type-Size	L	ID	ID1	DN	Weight	Art.Nr.
MT / VT	150	197	53.4	54	40	2870	**SKK 150 EA**
MT / VT	200	216	63	63.8	50	4039	**SKK 200 EA**
Automatic-Run-Out-Valves also available separately (7 bore)						160	**EWV 34**
Automatic-Run-Out-Valves also available separately (1 bore)						170	**EWV 341**
Opening pressure of valves approx. 1 bar!							

High-Pressure Screwings

made of Zinc-plated Steel

- Thread Stems for long-term steady installations of pipe and hose lines, extremely robust execution
- Female thread stems with swivelling nut, flat sealing with thread sealing ring
- Appropriate safety clamps and crimping ferrules (page 326)

Materials:

- Hose stem: Steel zinc-plated and blue passivated
- Seals: PUR

Max. Working Pressure	Temperature	Thread	Media	
PN 60 bar	-40°C – +95°C	ISO 228 / DIN 2999	liquid media	1



Male thread screwings for flat hoses or thick-walled rubber hoses

Thread connection	Hose connection	SW	DN	Weight	Type No.
R 1 m	Hose i.D. 25-28	36	20	220	**SGA 100-T**
R 1 1/2 m	Hose i.D. 38-40	50	40	372	**SGA 150-T**
R 2 m	Hose i.D. 38-40	60	40	210	**SGA 200/150-T**
R 2 m	Hose i.D. 50-54	60	50	620	**SGA 200-T**



Female thread screwings for flat hoses or thick-walled rubber hoses (with screwing nut)

Thread connection	Hose connection	SW	DN	Weight	Type No.
G 1 f	Hose i.D. 25-28	41	20	250	**SGI 100-T**
G 1 1/2 f	Hose i.D. 38-40	55	40	390	**SGI 150-T**
G 2 f	Hose i.D. 50-54	70	50	640	**SGI 200-T**

Attention: For hose connection each 9 different stem profiles types and sizes are available as standard version! For each order the exact hose type and size and preferred assembly method has to be notified to be able to choose the right hose stem version! For new stem profiles: minimum quantity is 50 sets

Other sizes on request!