



fire brigade / disaster control industry

construction sites

agriculture

potable water

special products

accessories

ESCHBACH **AQUADUR**

Potable water hose

Flexible lay flat hose for potable water supply and foodgrade applications, as a temporary bypass for pipeline repair and for emergency water supply. Offers a tremendous resistance to abrasion. Circular woven jacket out of 100 % high tenacity polyester yarn with a thermoplastic Polyurethane liner and cover manufactured using the "Throughthe-weave-extrusion-process."



ADVANTAGES

- · Maintenance free, easy cleaning and disinfection
- No drying required
- Long-living
- · Protected against mechanical damages
- · Resistance to microbiological attack
- \cdot High resistant to ageing, weathering, ozone and UV

APPROVALS

- DVGW worksheet W270
- BS 6920-1:2000 (WRAS)

SERVICES

- Individual marking available
- Binding with international couplings available
 on request
- Other diameters on request
- Standard lengths 100 m and 200 m
- Available in lengths up to 500 m depending on diameter

Diameter Inch (mm)	weight g/m	Wall thickness mm	Burst pressure bar	Working pressure bar	Tensile strength* kg
1" (25)	160	1,7	50	17	1.200
2" (52)	475	2,6	50	17	5.500
3" (75)	780	2,9	50	17	8.400
4" (102)	1350	3,0	40	14	10.250

* Theoretical value

Changes in technical specification without prior notice