Micro Quick Connect Couplings

Series ESMC single shut-off

DN 2.7


















- One-hand quick connect couplings with smallest dimensions made of brass MS 58 plain/ nickel-plated
- Suitable for low vacuum at low couple force compared to all other compatible products
- On request, couplings also available with coloured anodised aluminium sleeves
- Can be used in multiple applications in pneumatics, measure, control and regulation technology

Materials

- Body, sleeve, valve body, valve, plug: Brass MS 58 plain/ nickel-plated
- Springs, retaining ring: Stainless steel 1.4310
- Balls: Stainless steel 1.3541
- Seals: NBR (other materials on request)

Max. Working Pressure	Pressure Temperature		Thread	Flow Rate	Operation Type of valve		Media	Area	9
PN 35 bar	-20°C - +100°C	2.7	ISO 228 / DIN 13	165 l/min	One-hand	Single shut-off	Air / Others	Europe	10

Couplings with ma	Couplings with male thread												
Thread connection	L	SW	D	L1	Weight	Type No. n. plated	Type No. plain						
M 5 m	26	9	10	5	9	ESMCN 5 A	ESMC 5 A						
G 1/8 m	28	11	10	7	12	ESMCN 18 A	ESMC 18 A						

Couplings with fer	Couplings with female thread												
Thread connection	L	SW	D	L1	Weight	Type No. n. plated	Type No. plain						
M 5 f	26	9	10	5	10	ESMCN 5 I	ESMC 5 I						
G 1/8 f	28	12	10	7	14	ESMCN 18 I	ESMC 18 I						

Couplings with ho	ose barb)				TIEVIL	
Hose connection	L	D	L1	Weight	Type No. n. plated	Type No. plain	
Hose i.D. 3	35	10	13	9	ESMCN 3 T	ESMC 3 T	
Hose i.D. 4	35	10	13	10	ESMCN 4 T	ESMC 4 T	
Hose i.D. 5	35	10	13	10	ESMCN 5 T	ESMC 5 T	

For hose clips type ZOS (@ page 130) or type HS (@ page 131)

Couplings with h	Couplings with hose squeeze nut												
Hose connection	L	SW	D	Weight	Type No. n. plated	Type No. plain							
Hose 3x4	33	9	10	15	ESMCN 34 TQ	ESMC 34 TQ							
Hose 3x5	33	9	10	15	ESMCN 3 TQ	ESMC 3 TQ							
Hose 4x6	32	9	10	15	ESMCN 4 TQ	ESMC 4 TQ							

Couplings wit	th ho	se sq	ueez	e nut	and b	ulkhead sc	rewing		NEWL
Hose connect.	L	SW	D	L1	SW1	G	Weight	Type No. n. plated	Type No. plain
Hose 3x4	45	12	10	17	11	M 7x0.5 m	26	ESMCN 34 TQSV	ESMC 34 TQSV
Hose 3x5	45	12	10	17	11	M 7x0.5 m	26	ESMCN 35 TQSV	ESMC 35 TQSV
Hose 4x6	45	12	10	17	12	M 8x0.5 m	26	ESMCN 4 TQSV	ESMC 4 TQSV


For hose clips type ZOS (@ page 130) or type HS (@ page 131)

Couplings wi	th l	ıose	bar	b an	d bu	lkhea	d screwing			NEWL
Hose connect.	L	SW	D	L1	L2	SW1	G	Weight	Type No. n. plated	Type No. plain
Hose i.D. 3	51	12	10	13	17	11	M 7x0.5 m	24	ESMCN 3 TSV	ESMC 3 TSV
Hose i.D. 4	51	12	10	13	17	11	M 7x0.5 m	24	ESMCN 4 TSV	ESMC 4 TSV
Hose i.D. 5	51	12	10	13	17	12	M 8x0.5 m	24	ESMCN 5 TSV	ESMC 5 TSV

Micro Quick Connect Couplings

single shut-off Series ESMC

DN 2.7



Plugs with male th	read						NEW
Thread connection	L	SW	L1	L2	Weight	Type No. n. plated	Type No. plain
M 5 m	18	7	5	10	3	ESMCN 5 NA	ESMC 5 NA
G 1/8 m	20	11	7	10	6	ESMCN 18 NA	ESMC 18 NA





Plugs with female	Plugs with female thread												
Thread connection	L	SW	L1	L2	Weight	Type No. n. plated	Type No. plain						
M 5 f	17	7	5	10	3	ESMCN 5 NI	ESMC 5 NI						
G 1/8 f	19	12	7	10	6	ESMCN 18 NI	ESMC 18 NI						





Plugs with hose b	arb					NETT				
Hose connection	L	D	L1	L2	Weight	Type No. n. plated	Type No. plain			
Hose i.D. 3	24	7	13	10	2	ESMCN 3 S	ESMC 3 S			
Hose i.D. 4	24	7	13	10	3	ESMCN 4 S	ESMC 4 S			
Hose i.D. 5	24	9	13	10	3	ESMCN 5 S	ESMC 5 S			
For hose clips type ZOS (⊚ page 130) or type HS (⊚ page 131)										





Plugs with hose so	queeze n	ut				MEMI
Hose connection	L	SW	L1	Weight	Type No. n. plated	Type No. plain
Hose 3x4	25	8	10	12	ESMCN 34 SQ	ESMC 34 SQ
Hose 3x5	25	8	10	12	ESMCN 3 SQ	ESMC 3 SQ
Hose 4x6	25	8	10	12	ESMCN 4 SQ	ESMC 4 SQ





Plugs with hos	e sq	ueeze	nut a	and b	Plugs with hose squeeze nut and bulkhead screwing													
Hose connect.	L	SW	L1	L2	SW1	G	Weight	Type No. n. plated	Type No. plain									
Hose 3x4	38	12	17	10	11	M 7x0.5 m	23	ESMCN 34 SQSV	ESMC 34 SQSV									
Hose 3x5	38	12	17	10	11	M 7x0.5 m	23	ESMCN 35 SQSV	ESMC 35 SQSV									
Hose 4x6	38	12	17	10	12	M 8x0.5 m	23	ESMCN 4 SQSV	ESMC 4 SQSV									





Plugs with hose barb and bulkhead screwing											
Hose connect.	L	SW	L1	L2	L3	SW1	G	Weight	Type No. n. plated	Type No. plain	
Hose i.D. 3	45	12	13	17	10	11	M 7x0.5 m	21	ESMCN 3 SSV	ESMC 3 SSV	
Hose i.D. 4	45	12	13	17	10	11	M 7x0.5 m	21	ESMCN 4 SSV	ESMC 4 SSV	
Hose i.D. 5	45	12	13	17	10	12	M 8x0.5 m	21	ESMCN 5 SSV	ESMC 5 SSV	



