Return Valves and Check Foot Valves with Strainer

made of Brass

- Return valves shut off water flows in one direction. Check foot valves are return valves assembled with a strainer.
- Avoid draining of the suction line, after pump has been switched off
- Perfectly tight hold even with very low pressure through Nitril rubber sealing
- Hostaform wedge with double central slide

Materials:

- Body: Brass MS 58 plain
- Valve: Nylon
- · Springs: Stainless steel
- Seals: Nitril

ı	Max. Working Pressure	Temperature	Opening pressure	Thread	Media	
	PN 16 bar	PN 16 bar up to +100°C		ISO 228	Water	1
Į	PN 16 bar	up to +100°C	approx 0.02 bar	150 228	vvater	!

Return Valves with female thread							
Thread connection	L	D	Weight	Type No.			
G 1/4 f	45	28.5	105	RSV 14			
G 3/8 f	45	28.5	93	RSV 38			
G 1/2 f	47.5	30	100	RSV 12			
G 3/4 f	53	37	159	RSV 34			
G 1 f	59	44.5	239	RSV 10			
G 1 1/4 f	66	56	348	RSV 54*			
G 1 1/2 f	71	62.5	450	RSV 15*			
G 2 f	80	78.5	730	RSV 20*			



Check Foot Valves with strainer, outlet with female thread							
Thread connection	L	D	Weight	Type No.			
G 3/8 f	89	28.5	90	FVMF 38			
G 1/2 f	90	29.5	110	FVMF 12			
G 3/4 f	101	37	165	FVMF 34			
G 1 f	115	44.5	245	FVMF 10			
G 1 1/4 f	126	56	390	FVMF 54*			
G 1 1/2 f	140	63	500	FVMF 15*			
G 2 f	165	78	800	FVMF 20*			
* Max. Working Pressure: 10 bar							



Thread Stems with Male Thread and Hose Squeeze Nut Ferrule

made of Brass for Water for Perfect Hose Assembly

- Easy hose assembly with thread ferrule, multiple use and detachable
- Hose assembly without dead space for optimised safety and hygiene standards
- No dirt accumulation between hose and hose barb
- According to DIN EN 14 424
- · Please note correct hose wall dimensions

Materials:

• Screw connection: Brass MS 58 plain

Max. Working Pressure

PN 25 bar		up to +95°C			ISO 228		Water		
Thread Stems with Male Thread and Hose Squeeze Nut Ferrule									
Hose connect. T	hread connection	L	SW	L1	SW1	Passage	Weight	Type No.	
13x3 - 13x3.8	G 1/2 m	52	22	12	24	10	92	GSA 12-13	
19x3.8 - 19x4.2	G 3/4 m	53.5	27	13	32	17	143	GSA 34-19	
25x4.4 - 25x5	G 1 m	58.5	36	14	41	22	252	GSA 10-25	
Assembly instructions for thread ferrules (www.ludecke.com)									

