



Material Handling Hoses

ESSENTIAL™ CEMENT MASTER SD



								
mm	mm	mm	Bar	Bar	mm	Kg/m	m	REF.
51	67	8	8	24	255	2.2	40	4691-16051
63	81	9	8	24	315	3.0	40	4691-16052
76	96	10	8	24	380	4.0	40	4691-16053
80	100	10	8	24	400	4.2	40	4691-16054
90	110	10	8	24	450	4.6	40	4691-16055
102	122	10	8	24	510	5.3	40	4691-16056
110	132	11	8	24	550	6.5	40	4691-16057
127	149	11	8	24	635	8.0	40	4691-16058
152	175	11.5	8	24	760	9.7	40	4691-16059
203	228	12.5	8	24	1015	14.8	40	4691-16060

RECOMMENDED FOR

Vacuum and pressure hose for pneumatic transport of dry cement, slurries, dust, limestone, wood chips, coal, sand, gravel, ground slate, asphalt roofing chips, metal shavings. Contains a static-conducting black rubber in the tube and a ground wire in the hose wall for static charge dissipation.

TUBE

Black, anti-static NR/BR based rubber

REINFORCEMENT

High tensile synthetic textile cord, steel wire helix, static wires

COVER

Black, anti-static NR/SBR based rubber, resistance to weather and abrasion

TEMPERATURE

-20°C to +80°C

BURST PRESSURE

> 24 bar

ELECTRICALLY CONDUCTIVE

$R < 10^6 \text{ Ohm}$

STANDARDS

DIN 53516

BRANDING TRANSFER LABEL

ESSENTIAL™ CEMENT MASTER SD - 8 BAR

