

PREMIUM™ DAIRY MASTER LITE SD



| mm | mm | mm | Bar | Bar | mm | Kg/m | m | REF. |
|-----|-----|-----|-----|-----|-----|------|----|------------|
| 32 | 44 | 6 | 10 | 30 | 160 | 1.0 | 40 | 3131-11051 |
| 38 | 50 | 6 | 10 | 30 | 190 | 1.2 | 40 | 3131-11052 |
| 40 | 52 | 6 | 10 | 30 | 200 | 1.3 | 40 | 3131-11053 |
| 45 | 58 | 6.5 | 10 | 30 | 225 | 1.5 | 40 | 3131-11054 |
| 51 | 65 | 7 | 10 | 30 | 255 | 2.0 | 40 | 3131-11055 |
| 63 | 77 | 7 | 10 | 30 | 315 | 2.4 | 40 | 3131-11056 |
| 76 | 90 | 7 | 10 | 30 | 380 | 3.1 | 40 | 3131-11057 |
| 102 | 118 | 8 | 10 | 30 | 510 | 4.8 | 40 | 3131-11058 |

RECOMMENDED FOR

Very flexible corrugated vacuum and pressure hose (SD) for food products. Tank truck, barge, ship, or storage tank transfer of a variety of food products such as animal fat, vegetable oil and other edible oils requiring FDA sanitary hose. Also suitable for ice cream and other dairy products.

TUBE

NBR based white food quality rubber, resistance to animal fat and vegetable oils

REINFORCEMENT

Synthetic, high tensile textile with steel wire helix

COVER

NBR based rubber, blue, corrugated and resistance to animal fat and vegetable oils

TEMPERATURE

-30°C to +90°C, intermittent up to +130 °C/ 30 minutes for cleaning.

BURST PRESSURE

> 30 Bar

STANDARDS

FDA, BfR, animal derived ingredient free

BRANDING TRANSFER LABEL

PREMIUM™ DAIRY MASTER LITE SD - FOOD 10 BAR

