

## ESSENTIAL™ CONCRETE MASTER D



| mm | mm | mm  | Bar | Bar | mm  | Kg/m | m  | REF.       |
|----|----|-----|-----|-----|-----|------|----|------------|
| 19 | 31 | 6   | 40  | 120 | 133 | 0.5  | 40 | 4129-11051 |
| 25 | 39 | 7   | 40  | 120 | 175 | 0.8  | 40 | 4129-11052 |
| 32 | 47 | 7.5 | 40  | 120 | 224 | 1.0  | 40 | 4129-11053 |
| 35 | 50 | 7.5 | 40  | 120 | 245 | 1.1  | 40 | 4129-11054 |
| 38 | 54 | 8   | 40  | 120 | 266 | 1.3  | 40 | 4129-11055 |
| 50 | 68 | 9   | 40  | 120 | 350 | 1.9  | 40 | 4129-11056 |
| 63 | 83 | 10  | 40  | 120 | 441 | 2.7  | 40 | 4129-11057 |

### RECOMMENDED FOR

Concrete pump hose for abrasive substances such as concrete mortar, cement, plaster, grout and cement applications, handling a multitude of materials being pumped to concrete structures, tunnel faces, swimming pools.

### TUBE

Black, anti-static NR/BR/SBR based rubber

### REINFORCEMENT

High tensile synthetic textile cord

### COVER

Black, anti-static NR/SBR based rubber, resistance to weather and abrasion.

### TEMPERATURE

-20°C to +70°C

### BURST PRESSURE

> 120 bar

### ELECTRICALLY CONDUCTIVE

$R < 10^6 \text{ Ohm}$

### STANDARDS

DIN 53516: ~70mm<sup>3</sup>

### BRANDING TRANSFER LABEL

ESSENTIAL™ CONCRETE MASTER D - 40 BAR

