












## Petroleum Transfer Hoses

### ESSENTIAL™ OIL MASTER SD



								
mm	mm	mm	Bar	Bar	mm	Kg/m	m	REF.
19	29	5	10	30	95	0.5	40	4688-14051
25	35	5	10	30	125	0.6	40	4688-14052
32	42	5	10	30	160	0.9	40	4688-14053
38	48	5	10	30	190	1.0	40	4688-14054
50	60	5	10	30	250	1.4	40	4688-14055
65	77	6	10	30	325	2.3	40	4688-14056
75	88	6.5	10	30	375	2.7	40	4688-14057
100	114	7	10	30	500	3.9	40	4688-14058
125	141	8	10	30	625	6.0	40	4688-14059
150	166	8	10	30	750	7.9	40	4688-14060

#### RECOMMENDED FOR

Vacuum and pressure hose (SD) for transfer of fuel oil and other petroleum based products in home delivery, commercial and industrial service or in low pressure return lines. Transfer of refined fuels (commercial gasoline and diesel fuel), oils and other petroleum products. Ideal for oilfield service truck use. Service life of transfer hoses can be extended by draining hoses after use. Max 50% aromatic content.

#### TUBE

Black NBR rubber, smooth and oil resistant

#### REINFORCEMENT

High tensile synthetic textile cord, steel wire helix, two crossing anti-static wires

#### COVER

CR rubber, black, smooth with cloth impression, good resistant to weather and abrasion, chemical and oil resistance

#### TEMPERATURE

-30°C to +100°C

#### BURST PRESSURE

> 30 bar

#### ELECTRICALLY CONDUCTIVE

R < 10<sup>6</sup> Ohm

#### BRANDING TRANSFER LABEL

ESSENTIAL™ OIL MASTER SD - 10 BAR Ω

