

ESSENTIAL™ WATER MASTER SD



mm	mm	mm	Bar	Bar	mm	Kg/m	m	REF.
25	35	5	10	30	125	0.7	40	4686-12001
25	35	5	10	30	125	0.7	61*	4686-12002
32	42	5	10	30	160	0.9	40	4686-12003
32	42	5	10	30	160	0.9	61*	4686-12004
38	48	5	10	30	190	1.1	40	4686-12005
38	48	5	10	30	190	1.1	61*	4686-12006
51	63	6	10	30	255	1.6	40	4686-12007
51	63	6	10	30	255	1.6	61*	4686-12008
63	76	6.5	10	30	315	2.3	40	4686-12009
63	76	6.5	10	30	315	2.3	61*	4686-12010
76	89	6.5	10	30	380	2.8	40	4686-12011
76	89	6.5	10	30	380	2.8	61*	4686-12012
102	116	7	10	30	510	3.9	40	4686-12013
102	116	7	10	30	510	3.9	61*	4686-12014
127	142	7.5	10	30	635	5.7	40	4686-12015
152	169	8.5	10	30	760	8.0	40	4686-12016
203	224	10.5	10	30	1015	12.9	40	4686-12017

* 61m coils are made to order

RECOMMENDED FOR

Vacuum and pressure hose (SD) for water, waste water, sea water, mud, slurry. Water suction in heavy duty service requiring a compact, rugged and lightweight hose.

TUBE

Black EPDM, smooth

REINFORCEMENT

Synthetic, high tensile textile with steel wire helix

COVER

EPDM rubber, black, good weather and aging resistance

TEMPERATURE

-35°C to +80°C

BURST PRESSURE

> 30 bar

BRANDING TRANSFER LABEL

ESSENTIAL™ WATER MASTER SD - 10 BAR

